



WARRANTY: 10 YEARS FOR PARTS AND LABOR!

**NORTH AMERICAN MADE PARTS TO MEET
NORTH AMERICAN CONDITIONS**

GANTRY CRANE SPECIFICATIONS										
Model	WLL (lb.)	PLA (lb.)	STD.	Custom	Height to Lift Ring		Caster	Assembled	Hole Space (in.)	Assembled Max Height (in.)
			Beam (ft.)	Beam (ft.)	Min. (in.)	Max. (in.)	Size (in.)	Weight lb.		
1100R	1100	1650	8	6 - 30	66	90	6	185	6	106
2200R	2200	3300	8	6 - 20	66	90	6	195	6	106
2200LW	2200	3300	10	6 - 20	90	122	6	225	8	138
4400M	4400	6600	8	6 - 15	66	90	6	240	6	106
4400R	4400	6600	12	6 - 15	90	122	6	275	8	138
4400T	4400	6600	15	6 - 15	96	136	8	325	8	152
6600R	6600	9900	15	6 - 15	106	154	8	595	8	174
8800R	8800	13200	13'6"	6 - 13'6"	106	154	8	680	8	174
10000R	10000	15000	12' 6"	6 - 12'6"	106	154	8	670	8	174
11000R	11000	16500	10	6 - 10	106	154	8	650	8	174

**Assembled Weight includes standard Locking 'Surround-Beam' Trolley
Custom Height Models Available**

Specialty Models

Winch-Equipped Gantry



Winch-equipped Gantry designed to place and retrieve cameras from deep sewer lines. Winch also used to lower tools and supplies down shafts.

Cantilever-Beam Gantry



Cantilever-Beam Gantry can be used for lifting loads over the side of tanks, walls, etc. Lift capacity is 900 lbs./410 kg., Cantilever reach is 24 in./955 mm.

Easily Moved Equipment Inc.
134 Albany Street, Fort Erie, ON L2A 1L6
Telephone: 888-679-5283 Fax: 905-991-0006
Email: info@easilymovedequipment.com
Web: www.easilymovedequipment.com

**D
E
A
L
E
R** **Allstate Crane Rental, Inc.**
Goose Creek, SC
Tel: 843-572-1697
Toll Free: 800-982-3499

'Engineered maintenance equipment is our business.'